

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number  
**WO 2005/005071 A1**

(51) International Patent Classification<sup>7</sup>: **B21D 5/14**  
(21) International Application Number:  
PCT/SR2004/001063  
(22) International Filing Date: 1 July 2004 (01.07.2004)  
(25) Filing Language: Swedish  
(26) Publication Language: English  
(30) Priority Data:  
0302082-3 10 July 2003 (10.07.2003) SE

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HK, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): ORTIC AB [SE/SE]; Tunavägen 290, S-781 73 Borlänge (SE).  
(72) Inventor; and  
(75) Inventor/Applicant (for US only): INGVARSSON, Lars [SE/SE]; Myntgatan 3, S-784 54 Borlänge (SE).  
(74) Agent: ÅSLUND, Roland; Avesta Patentbyrå, P.O. Box 99, S-775 01 Krylbo (SE).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A MACHINE FOR BENDING OF LONG PRODUCTS AND A METHOD TO CONTROL SUCH A MACHINE



(57) Abstract: A machine is process monitored and controlled for continuous bending of long products to a predetermined radius by using three parallel contact-free distance meters (laser transmitters) and by measuring the distances to the bent surface on the product, by calculating the actual bending radius based on the fixed distances between the meters and the measured distances, and controlling the adjustment of the machine in response to the relation between the calculated actual radius and the desired radius. The machine comprises a processor for performing said calculation and controlling the bending device.

WO 2005/005071 A1